

Amendments to the Substitute Specification:

Please replace the fourth paragraph beginning on page 4 and spanning over to page 5 of the Substitute Specification as follows:

Figure 3 is a schematic illustration of the phone 2. The phone 2 has the previously described antenna 16, voice dial button 22, on/off button 24, input device (joystick) 28, hinge switch 30, easily accessible button 36, microphone 18, display 26, speakers 40 and 38. In addition the phone has a processor 44, a transceiver 46 and a memory 48. The antenna 16 is connected to the transceiver 46. The transceiver has reception circuitry for receiving radio frequency signals encoded with data. It processes the received signals as is known in the art to provide the data in digital form to the processor-5044. This data may be a voice message or part of a phone conversation in which case the processor controls the speaker 40 to provide an audible output to the user. Alternatively the data may be part of an alphanumeric message in which case the processor 44 is operable to provide the message on the display. The transceiver has transmission circuitry which is provided with digital data from the processor 44 which may have been input via the microphone 18 or via the input device 28 as alphanumeric characters. The transmission circuitry produces radio frequency signals encoded with that data. The processor is connected to memory 48 to which it can write and from which it can read. The memory 48 typically stores software which controls the functioning of the processor and the phone. In particular the software controls how the processor responds to inputs and what outputs it provides.